

# United States Masters Swimming

## POOL LENGTH CERTIFICATION FORM

1. **Pool Name:** Adamsville Natatorium **LMSC:** Georgia  
**Address:** 3201 M.L. King Drive NW  
**City:** Atlanta **State:** Georgia **Zip:** 30311

2. **Measurement parameters**

- a. Nominal pool length:  25 yards  25 meters  50 meters  
b. Moveable bulkhead:  yes  no  
c. Measuring device (see below):  Steel tape  Laser  Other  
d. Number of touchpads per lane at time of measurement:  None  One  Two  
(In some cases, two touchpads may be used, one at each end of the pool.)

3. **Measurements:** (Minimum distances measured)

Distanced measured in:  feet/inches  meters/centimeters

If these measurements are a confirmation of bulkhead placement, only the outermost lanes and a center lane must be measured.

Lane 1 75'.026	Lane 2 75'.024	Lane 3 75'.02	Lane 4 75'.02
Lane 5 75'.02	Lane 6 75'.02	Lane 7 75'.019	Lane 8 75'.016
Lane 9	Lane 10	Lane 11	Lane 12

4. **Measured by:**

**Name:** Edward Saltzman  
**Title:** LMSC Official's Chair  
**Address:** 5060 Cameron Forest Parkway  
**City:** Alpharetta  
**State:** Georgia **Zip:** 30022  
**Date:** 11/11/12

**Submitted by:**

**Name:** Edward Saltzman  
**Title:** LMSC Records Chair  
**Address:** 5060 Cameron Forest Parkway  
**City:** Alpharetta  
**State:** Georgia **Zip:** 30022  
**Date:** 11/11/12

**Measurement procedures:**

- Note that existing certification forms may be used either from the pool or from USA-S, as long as all lanes have been measured.
- A 25 meter pool measures 82 feet 0.25 inches, A 50 meter pool measures 164 feet 0.50 inches
- Measurements must be conducted using a measuring device with the minimum measuring quality of a steel tape, at least  $\pm 0.005$  m ( $\pm 0.20$  inches or 0.016 feet), over the nominal distance. A laser measuring device may be used, but it must be as accurate as required for steel tapes.
- Tapes may not be combined to perform the measurements.
- Measurements may be reported in either the English system (feet/inches) or the metric system (meters/centimeters).
- One measurement must be conducted for each lane of competition.
- Inspect each end of the pool. If there are any protrusions in a lane from 0.8 meters below the surface to the top of the touch pad or wall or up to 0.3 meters above the surface whichever is higher, you must use the protrusion as the measurement point. Otherwise, measurements must be taken in the center of each lane at water level.
- Measurements may be conducted with or without touchpads in place.
- Permanent courses need only be measured once unless structural changes have occurred since original measurement.
- For a pool with a moveable bulkhead, course measurement must be confirmed by a responsible person at the conclusion of the session.

**Maintaining Pool Length Certification Forms is an LMSC responsibility. Completed forms should be sent to the Top Ten Chairperson for the LMSC. Attach a copy of this form to record applications if the form is not already on file with the National Chairperson.**